



METHOD AND DEVICE FOR RECORDING INFORMATION IN UNITS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This is a continuation application of prior U.S. Patent Application Serial No. 09/601,754, filed August 7, 2000, now U.S. Patent 6,628,583.

5

BACKGROUND OF THE INVENTION

Field Of The Invention

[0002] The invention relates to a method of recording an information signal representing at least one information unit on a record carrier having a recording track ~~which comprises~~ comprising pre-formed track position information indicative of predefined locations for consecutively recording the information units, and a first one of said locations comprising an earlier recorded information signal, ~~said the method comprising the steps of~~ generating, from the information signal, a modulated signal having successive frames, each frame including a synchronizing signal, and scanning said recording track and recording the modulated signal at a second one of said locations, while controlling such recording so as to maintain a fixed relationship between the track position information and the synchronizing signals.

[0003] The invention further relates to a device for recording an information signal representing at least one information unit on a record carrier having a recording track ~~which comprises~~ comprising

pre-formed track position information indicative of predefined locations for consecutively recording the information units, and a first one of said locations comprising an earlier recorded information signal, the device comprising modulation means for generating, from the information signal, a modulated signal having successive frames, each frame including a synchronizing signal, and recording means for scanning said recording track and recording the modulated signal at a second one of said locations, ~~and for said~~ recording means maintaining, during said recording, a fixed relationship between the track position information and the synchronizing signals.

#### Description Of The Related Art

[0004] A method and apparatus for successively recording information signals on a record carrier is known from U.S. Patent 5,187,699. The information signal is modulated to form a modulated signal having a frame structure comprising synchronizing signals for positioning the modulated signal in the track at predefined locations indicated by prerecorded track position information. The process of consecutively recording signals in adjacent areas in a track on the record carrier, is called linking. In the known linking method, after a first recording signal is completely recorded, the recording process is continued after the last frame of the modulated signal up to a link position. When a next information signal is to be recorded, the recording process is

started at the link position by recording dummy information (usually zero data) up to the start of the following predefined location. Hence, the signal prior to the first frame synchronizing signal of said following location does not contain valid information. As a result, a ~~so~~-so-called linking block is created between the first recorded signal and the second recorded signal, ~~which this linking block includes including~~ said link position. Hence, the linking block does not contain valid recorded information, and its data storage capacity is lost.

10

#### SUMMARY OF THE INVENTION

[0005] It is an object of the invention to provide a recording method and device in which linking is more efficient.

15

[0006] For this purpose, the method as described in the opening paragraph is characterized in that in the event that the second one of said locations is after and adjacent to the first one of said locations, the recording is started before the end of a last frame of the earlier recorded information signal at a first predefined distance before a first synchronizing signal of the modulated signal.

20

[0007] Further, the device as described in the opening paragraph is characterized in that the recording means ~~are arranged for determining~~ determines if the second one of said locations is after

25

and adjacent to the first one of said locations, and, in such event, ~~starting~~ starts the recording before the end of a last frame of the earlier recorded information signal at a first predefined distance before a first synchronizing signal of the modulated  
5 signal. By starting the recording within the last part of the earlier recorded signal, the signal in the next, adjacent area, i.e., said second location, is positioned at the nominal position and includes, completely, the first synchronizing signal as required by decoding circuits to decode the new data recorded at  
10 the second location. Hence, the modulated signal at the second location is completely decodable. In fact, the link position is located within the existing recorded information, and, consequently, the modulated signal at the first location is damaged in the very last part. Although this causes a few errors in the  
15 last symbols of the earlier recorded information unit, this proves to be preferable to ~~losing~~ losing an entire linking block. The errors may be acceptable for the system, or a system of error protection may be applied to correct ~~said~~ these errors. The measures according to the invention have the advantage, that no  
20 linking block is created and no storage capacity is lost, because the second location, comprising the last recorded signal, is directly adjacent to the first location comprising the previously existing signal. In addition, any recorded data stream is not interrupted by invalid data from the linking block, which provides

better compatibility with existing read-only record carriers, e.g., DVD-ROM or DVD-VIDEO.

[0008] The invention is also based on the following recognition. Usual channel coding and decoding systems are arranged to operate on symbols (e.g., 8 or 16 channel bits). When, during decoding, a read signal from the link position is decoded, the decoder will be confronted with a shift of the symbol boundary, a ~~so~~-so-called bit slip of a few bits, because it is, in practice, hardly possible to start the recording process with an accuracy of less than one bit. As a result, the decoder will detect errors in all symbols for the full remaining part of the frame up to the next synchronizing signal. In prior art systems, this posed no problem, as the linking block did not contain useful data. However, the inventors have seen, that by selecting the linking point in the last part of the existing frame, only a few errors would arise, which further may be correctable by modern error correcting codes.

[0009] A preferred embodiment of the device, wherein the recording means terminates the recording before the modulated signal is completely recorded at a second predefined distance before a nominal position of a first synchronizing signal of an information signal at the subsequent one of said locations, ~~according to claim 4~~ has the advantage, in the event that a new recording is to be made before and adjacent to an existing one, that the first synchronizing signal of the existing recording is

not damaged, and only a predictable and low number of errors is generated when decoding the last recorded signal.

[0010] A preferred embodiment of the device, wherein the recording means variably selects the first predefined distance between a minimum and a maximum value, while maintaining the position of the first synchronizing signal, ~~according to claim 9~~ has the advantage, that the physical starting point of recording is varied. This has the effect that disturbing read signal values are prevented, while the data is not shifted from its actual position.

[0011] A preferred embodiment of the device, wherein the recording means records variable random data in the interval between the predetermined distance and the first synchronizing signal, ~~according to claim 10~~ has the advantage that, by using variable random data instead of a fixed pattern in said interval, the sign of the synchronizing signal is also randomly varied for subsequent overwrite cycles of the same location. Hence, material defects in the recording layer of said location due to repeated writing of the same patterns are counteracted.

~~Further advantageous, preferred embodiments according to the invention are given in the further dependent claims.~~

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0012] These and other aspects of the invention will be apparent from and elucidated further with reference to the embodiments

described, by way of example, in the following description and with reference to the accompanying drawings, in which:

[0013] Figures 1a and 1b shows a record carrier<sub>Ti</sub>

[0014] Figure 2 shows a recording device<sub>Ti</sub>

5 [0015] Figure 3 shows the link position due to recording block N after block N-1<sub>Ti</sub>

[0016] Figure 4 shows consecutive frames for continuous recording<sub>i</sub>

10 [0017] Figure 5 shows the link position for recording block N after a recorded location<sub>Ti</sub>

[0018] Figure 6 shows the start position for recording block N after an unrecorded location<sub>Ti</sub>

[0019] Figure 7 shows the end position for recording block N before a recorded location<sub>Ti</sub>

15 [0020] Figure 8a shows read signal effects of overwriting at a fixed position, while

[0021]—Figure 8b shows read signal effects of overwriting at a changing position<sub>Ti</sub> and

20 [0022] Figure 9 shows a flowchart of a recording method for successively recording information signals.

[0023] Corresponding elements in different Figures have identical reference numerals.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0024] Figure 1a shows a disc-shaped record carrier 11 having a track 9 and a central hole 10. The track 9 is arranged in accordance with a spiral pattern of turns, constituting substantially parallel tracks, on an information layer. The record carrier may be optically readable, called an optical disc, and has an information layer of a recordable type. Examples of a recordable disc are the CD-R and CD-RW, and writable versions of DVD, such as DVD+RW. The information is represented on the information layer by recording optically detectable marks along the track, e.g., crystalline or amorphous marks in phase change material. The track 9 on the recordable type of record carrier is indicated by a pre-embossed track structure provided during manufacture of the blank record carrier. The track structure is constituted, for example, by a pre-groove 14 which enables a read/write head to follow the track during scanning. The track structure comprises position information, e.g., addresses, for indication the location of units of information, usually called blocks. The position information may include specific synchronizing marks for locating the start of such units.

[0025] Figure 1b is a cross-section taken along the line b-b in Figure 1a of the record carrier 11 of the recordable type, in which a transparent substrate 15 is provided with a recording layer 16 and a protective layer 17. The pre-groove 14 may be implemented as an indentation or an elevation, or as a material property deviating from its surroundings.



[0026] The record carrier 11 is intended for carrying information represented by modulated signals comprising frames. A frame is a predefined amount of data preceded by a synchronizing signal. Usually, such frames also comprise error correction codes, e.g., parity words. An example of such a recording system is known from the DVD system, in which the frames carry 172 data words and 10 parity words, ~~which this example is being used~~ in the description below. The data is organized in units comprising a number of frames which contain Error Correction Codes (ECC) for correcting errors in the user information in the unit. In DVD, the size of such a unit is 32KB user data, ~~and~~ contains 2 layers of error correction, and is called a block. The first layer of error correction (called C1) corrects small errors, like random errors, and the second layer (called C2) corrects the large error, such as burst errors. A drive should be able to write and/or rewrite such a block independently. According to the invention, no blocks are used for linking only, all blocks are used to store user data. This means that a link position should be defined in order to guarantee data integrity. There will always be some errors on a link position, but the goal is to minimize the amount of errors on such a link position. The following items are important for the choice of the link position:

- The accuracy of the writing (in channel bits) which can be achieved with respect to the data already written on the disc;
- The effect of a few bit errors on the error correction;

- The content of the data written on the link position<sub>7</sub>; and
- The physical damage caused by overwriting<sub>1</sub> each time<sub>1</sub> the same data.

[0027] A main consideration is<sub>7</sub> that if a bit slip occurs in  
5 combination with data<sub>7</sub> which is protected with error correction,  
then the position of the bit slip is very important. For DVD<sub>1</sub> the  
data is divided in-to ECC units of 32KB, while the error correction  
operates on channel words or bytes. If (e.g.<sub>1</sub> after the linking  
point) the word boundary is shifted one or a few bits, all words  
10 are different, and no error correction can take place. This is  
called bit slip. A C1 code word means one row of the error  
correction and is able to detect and correct errors. A bit slip at  
the beginning of a C1 code word will destroy all the bytes after  
the bit slip. The error correction capability is limited and the  
15 result is that the whole C1 code word is not correctable. Now the  
second layer (C2) is required to correct the errors. When the  
bit slip occurs at the end of a C1 code word<sub>1</sub> then the amount of  
errors is limited and the error correction will be able to correct  
the errors. The second layer of error correction is not required  
20 for the correction of errors and can be used for other errors. So<sub>1</sub>  
a link position is preferable positioned at the end of the last C1  
code word of the previous ECC unit.

[0028] Figure 3 shows the link position due to recording block N  
after block N-1. The link position 31 is indicated by a dashed line  
25 at 32 channel bits before the synchronizing signal 30, in the DVD

format called Sy0. For DVD, the first error correction layer consists of 172 data bytes and 10 parity bytes. With 10 parity bytes, a maximum of 5 byte errors can be corrected, but a more practical limit is less than or equal to 4 byte errors. The result of this insight is to position the linking of ECC block N-1 and ECC block N after the last 4 bytes of ECC block N-1 and before the start of block N. The position shown at 32 channel bits corresponds to 2 bytes (as one byte has 16 channel bits in DVD), which gives the maximum tolerance for link position inaccuracies. In general, the link position may be selected as close as possible before the synchronization signal, while making sure that despite the start of write link position inaccuracies in forward direction, the new information always overwrites the old synchronization signal. Correspondingly, at the end of write, before an already existing information unit, the new information should never damage the next synchronization signal of said already existing information unit. The last channel words of an information unit usually represent parity symbols (called parity bytes above), and hence, the minimal number of parity symbols is damaged. In an embodiment, the linking errors can be limited to errors within one symbol, when the expected link position inaccuracies in forward and backward direction are limited to within one channel word. The link position is then set within the last channel word before the synchronizing signal, taking into account the maximal forward and backward inaccuracies. A practical value for such a link position is the

middle of the last channel word, when a symmetrical pattern of forward and backward link position inaccuracies is expected. For a channel word of 16 channel bits, this amounts to 8 channel bits before the end of the information unit.

5    [0029]    Figure 2 shows a recording device for writing information on a record carrier 11 of a type which is (re)writable. The device is provided with recording means for scanning the track on the record carrier, including drive means 21 for rotating the record carrier 11, a head 22, positioning means 25 for coarsely  
10   positioning the head 22 in the radial direction on the track, and a control unit 20. The head 22 comprises an optical system of a known type for generating a radiation beam 24 guided through optical elements focused to a radiation spot 23 on a track of the information layer of the record carrier. The radiation beam 24 is  
15   generated by a radiation source, e.g., a laser diode. The head 22 further comprises a focusing actuator for moving the focus of the radiation beam 24 along the optical axis of ~~said~~ the beam and a tracking actuator for fine positioning of the spot 23 in a radial direction on the center of the track. The tracking actuator may  
20   comprise coils for radially moving an optical element, or may be arranged for changing the angle of a reflecting element. For writing information, the radiation is controlled to create optically detectable marks in the recording layer. For reading, the radiation reflected by the information layer is detected by a  
25   detector of a usual type, e.g., a four-quadrant diode, in the head

22 for generating a read signal and further detector signals including a tracking error and a focusing error signal coupled to ~~said the~~ tracking and focusing actuators. The read signal is processed by a reading means of a usual type (not shown) to  
5 retrieve the information. The device comprises means for processing ~~the input~~ information to generate a write signal to drive the head 22, ~~which comprisethe processing means comprising~~ an input unit 27, a formatting unit 28, and a modulation unit 29. The control unit 20 controls the recording and retrieving of information and may be  
10 arranged for receiving commands from a user or from a host computer. The control unit 20 is connected via control lines 26, e.g., a system bus, to ~~said the processing~~ means and to the drive means 21, and the positioning means 25. The control unit 20 comprises control circuitry, for example, a microprocessor, a  
15 program memory and control gates, for performing the procedures and functions according to the invention as described below with reference to Figure 3. The control unit 20 may also be implemented as a state machine in logic circuits. During the writing operation, marks representing the information are formed on the record  
20 carrier. The marks may be in any optically readable form, e.g., in the form of areas with a reflection coefficient different from their surroundings, obtained when recording in materials, such as dye, alloy or phase change material, or in the form of areas with a direction of magnetization different from their surroundings,  
25 obtained when recording in magneto-optical material. Writing and

reading of information for recording on optical disks and usable  
formatting, error correcting and channel coding rules are well-  
known in the art, e.g., from the CD system. The marks can be formed  
by means of the spot 23 generated on the recording layer via the  
5 beam 24 of electromagnetic radiation, usually from a laser diode.  
User information is presented on the input unit 27, which may  
~~comprise of~~include compression means for input signals, such as  
analog audio and/or video, or digital uncompressed audio/video.  
Suitable compression means are described for audio in WO 98/16014-  
10 A1, corresponding to U.S. Patents 6,269,338 and 6,778,965 (PHN  
16452), and for video in the MPEG2 standard. The input unit 27  
processes the audio and/or video to unit of information, which are  
passed to the formatting unit 28 for adding control data and  
formatting the data according to the recording format, e.g., by  
15 adding error correction codes (ECC). For computer applications,  
units of information may be interfaced to the formatting unit 28  
directly. The formatted data from the output of the formatting unit  
28 is passed to the modulation unit 29, which comprises, for  
example, a channel coder, for generating a modulated signal which  
20 drives the head 22. Further, the modulation unit 29 comprises  
synchronizing means for including synchronizing patterns in the  
modulated signal. The formatted units, presented to the input of  
the modulation unit 29, comprise address information and are  
written to corresponding addressable locations on the record  
25 carrier under the control of control unit 20. Usually, the

recording apparatus will also be arranged for reading, i.e., having the reading and decoding means of a playback apparatus and a combined write/read head.

[0030] According to the invention, the control unit 20 of the recording device, as shown in Figure 2, is arranged for recording the information according to the methods described below with reference to the Figures 4 to 7. The modes of writing are defined for different situations. The start/stop or continuous writing modes are defined separately; four different writing modes are defined: Continuous writing, Start of writing when the previous location is already written, Start of writing when the previous location is erased or not written, and End of writing.

[0031] Figure 4 shows consecutive frames for continuous recording. No special action is required. The recorder continually records from block N-1 to block N without special action.

[0032] Figure 5 shows the link position for recording block N after a recorded location. The link position is selected at a predefined distance before the first synchronizing signal of the new frame. The predefined distance is relatively short (at least in the second half of the frame), but actually much closer to the end, so as to minimize the number of errors. For recording DVD, the link position may be positioned after byte 178 of the last C1 code word of the previous ECC unit and before the start of the next ECC unit, i.e., the synchronizing signal Sy0. In an embodiment, the data to

be written before the new data start is chosen randomly, which is important for the interaction between old and new data for phase change recording. Writing, each time, exactly the same data over each other limits the amount of overwrite cycles. Therefore, the following measures, separate or in combination, may be included:-

- The data in the linking area can be chosen random. This will prevent overwriting, each time, the same data in the linking area.

An advantage of using random data is important when the new ECC unit contains always exactly the same data. The random data will cause always of different start value of the Digital Sum Value (DSV) at the beginning of the new ECC unit. The different values of the DSV cause differences in the following signal even when the data is not changed, and this improves the number of overwrite cycles of the data; and

- A small random shift of the link position can be introduced to improve the direct overwrite cycles.

**[0033]** In Figure 5, a distance  $x$ , in error symbols ( $0 < x < 5$ ), is indicated for the linking distance. As discussed above, the distance  $x$  must be shorter than the number of error symbols which can be corrected. Of course, the actual distance may have any value in channel bits, which results in said number of correctable symbols, as long as the spread in this distance due to linking inaccuracies does not damage the next synchronization signal Sy0. It may be acceptable that, in some cases, even the beginning of the Sy0 synchronizing pattern is damaged, as long as the special mark



(or marks) within the synchronizing pattern, e.g., a long mark I14 of run-length 14 channel bits, is not damaged, because such special marks are used for detecting the synchronizing patterns.

[0034] Figure 6 shows the start position for recording block N after an unrecorded location. When no data is written on the disc at the position of the previous ECC block, then the recording should start at least a few hundred channel bits before the new ECC block starts. But the longer the better, because the channel electronics (e.g., a PLL/Slicer/Sync detection) needs time to adjust and synchronize. When at least 3 three sync frames are recorded, then the flywheel construction of the sync is already working. In this case, random data is written, but the sync patterns are, of course, embedded in the proper positions. In a practical embodiment, a full information unit (e.g., a full ECC block) is added as dummy unit. The dummy unit may, for example, be filled with random data, or may be just repeating the data of recording block N. Adding the dummy unit does not require extra settings or dedicated formatting rules in the formatting unit 28, but only additional steps in the control unit 20 for starting the writing process one information unit earlier, in the event that the recording block N is after an unrecorded area. The status of the area N - 1 before area N may be known from disc control data, e.g., a table of recorded and unrecorded areas on the disc, or detected by the device just before the writing of area N. Such disc control data may be generated, stored and updated by the device itself, or

by a software disc operating system in controlling computer system. In an embodiment, the writing of the dummy unit on position N - 1 may be started at a further predefined and different link position, e.g., at a relatively short distance after the synchronization signal of unit N - 1. Thereby, damage inflicted upon a unit (possibly) already recorded in position N - 2 is prevented. For example, the device moves the head to the beginning of position N - 1 and starts reading. If no earlier recorded signal is detected, the recording of dummy unit is started at some distance after the start of the area N - 1. However, if an earlier recorded signal is detected, the reading operation is continued up to said predefined distance before the end of area N - 1 and the writing is started there, i.e., at the predefined distance before the synchronization signal of the next frame, which is the first frame of block N.

**[0035]** Figure 7 shows the end position for recording block N before a recorded location. The end of writing is preferable as short as possible before the position of the next ECC block, because then the error correction has the minimum number of errors to correct. The remaining number of undamaged parity symbols x is indicated to be between 5 and 10, for example, for DVD, indicating that at least half the available number is undamaged.

**[0036]** Figure 8a shows read signal effects 81 of overwriting at a fixed position, while Figure 8b shows read signal effects 82 of overwriting at a changing position. The read signal is affected by the exact position of the linking in repeated overwriting. For

rewritable optical discs, the phase change material is very often used to record the data. A known phenomena in phase change recording is material flow. When the start of a recording, ~~in~~ in-phase change material always starts at the same position (within a few channel bits) then large fluctuations in the signal level will occur after many overwrite cycles, as shown in Figure 8A. This is not a desired situation. Some improvement can be achieved by shifting the data randomly more than a few channel bits. But now, the idea is not to start at the same position each time, but randomly vary this start position of the recording, while the physical position of the data in the next frame is not altered. Hence, the synchronizing signal is located at its nominal position. For example, ~~T~~, the first recording starts at byte number 180 of the last C1 code word of the previous ECC unit and will write 2 bytes before the first C1 code word of the next ECC unit starts. The second recording (at that same location) starts at byte number 178 of the last C1 code word of the previous ECC unit, and writes 4 bytes before the first C1 code word of the next ECC unit starts. The result is a variable start position of the recording while the position of the further data is not changed. The random variation may be selected to have any number of channel bits. The maximum and minimum distance should result in an amount of errors within the error correction capability. A practical implementation is a random selection between a minimum and a maximum distance.

[0037] Figure 9 shows a recording method for successively recording information signals. It is assumed that a record carrier of a writable type is inserted in a recording device, and that it already contains some recorded information. In a first step 91 (COMMAND), a command is received to record block N. In a second step 92 (SCAN), the track on the record carrier is scanned up to the preceding location of block N-1. In a first test 93, it is decided, if the preceding location is not blank (i.e., contains already some information signal). If NOT BLANK, in a step 95, a start position is determined at a first predetermined distance, as described above with reference to Figure 5. If no information signal is present on the preceding location, in a step 94, a long sequence of dummy data is recorded before the start of location N to enable any read circuit to lock to the data as described with reference to Figure 6. In step 96, after said steps 94 or 95, the actual block N (or several continuous blocks as described with reference to Figure 4) are recorded. In test 97, the status of the location N+1 after block N is determined. This may be accomplished by scanning the track before the recording is started, e.g., in step 92. Alternatively, a special table may be present on the record carrier or in the device which keeps track of unrecorded and recorded areas, e.g., in the file management system. In the event that no signal is recorded after block N (or the signal has no valid status, e.g. erased), in a step, the recording process is continued at least until the modulated signal of block N is

completely recorded, and it may be continued for some predetermined distance after the last frame to prevent any read circuit from detecting a read error prematurely. In the event that the next location N+1 contains a valid information signal, in a step 99, the recording process is stopped at a second predetermined distance before the modulated signal of block N is completely recorded as described with reference to Figure 7. After steps 98 or 99, the recording of block N is completed, and a next command may be awaited.

10 [0038] In an embodiment, the test 97 is omitted and the recording process is always stopped at a short predetermined distance before the nominal position of the start of the synchronizing signal of the next block. In addition, the above embodiments may be arranged to select the second predetermined distance always shorter than the first predetermined distance. This has the advantageous effect, that no unrecorded gaps will exist between successively recorded blocks. It is to be noted that starting and ending point inaccuracies must be taken into account.

15 [0039] Although the invention has been explained by embodiments using the DVD-optical recording format, it may be applied for any format for recording units of information. For example, the record carrier may also be a magnetic type disc or a tape. It is noted, that in this document, the word 'comprising' does not exclude the presence of ~~ether~~ elements or steps other than those listed, and  
25 the word 'a' or 'an' preceding an element does not exclude the

PHN 17,399A

presence of a plurality of such elements, that any reference signs do not limit the scope of the claims, that the invention may be implemented by means of both hardware and software, and that several 'means' may be represented by the same item of hardware.

- 5 Further, the scope of the invention is not limited to the embodiments, and the invention lies in each and every novel feature or combination of features described above.

ABSTRACT+ OF THE DISCLOSURE

A method and device for recording information signals on a partly recorded writable record carrier (11), e.g., an optical disc. An information signal represents at least one information unit. The record carrier has a recording track which ~~comprises~~ includes pre-formed track position information indicative of locations for recording the information units. From the information signal, a modulated signal is generated having successive frames, each frame including a synchronizing signal. The modulated signal is recorded at a one of ~~said the~~ locations, while maintaining a fixed relationship between the track position information and the synchronizing signals. In the event that the location is after and adjacent to an already recorded location, the recording is started at a link position (31) before the end of a last frame of the earlier recorded information signal, at a predefined distance before a first synchronizing signal (30) of the modulated signal.

~~Figure 3~~